SAFETY DATA SHEET

	SAFETI DA	TA SHEET			
PRODUCT NAME: Epoxy.com Produc PRODUCT CODE:	t #203 PAB	RT A			ES: H F R P
				1	1 0 B
SECTION 1:	MANUFACT	URER IDENT	IFICATI	ON	
ADDRESS: 20774	Systems, 2 W. Pennsy lon, FL	lvania Ave.			
EMERGENCY NUMBER: 1-800-633 INFORMATION NUMBER: 1-352-489		DATE PRI PREPARER		6/2010 N. Lamber	st
SECTION	2: HAZAR	DOUS INGRE	DIENTS		
			ACGIH		
Resin250Alkyl Glycidyl Ether120Alkyl Phenol848Benzyl Alcohol10Substances listed are presentcited as a potential Carcinoge	n in the (NE NE tration of OSHA hazard	ls commu	nication	NO NO NO or 0.1% if standard.
Where proprietary ingredient i in 29 CFR 1910.1200.	s listed,	the identi	ty is a	vailable	as provided
NE - Not Established					
SECTION 3: PH	HYSICAL/CH	EMICAL CHAI	RACTERIS	STICS	
BOILING POINTAbove 400° FVAPOR DENSITYApprox. 3.5 (Air = 1)VAPOR PRESSURELess than 1 mm Hg @ 100° FVOC0.00SOLUBILITY IN WATERVery slightAPPEARANCE AND ODORLow viscosity clear liquid with a mild, pleasant aromaSPECIFIC GRAVITY (H20=1)1.11					
SECTION 4: FIRE AND EXPLOSION HAZARD DATA					
<pre>FLASH POINT: >200° F METHOD USED: Closed Cup FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: Not determined UPPER: Not determined EXTINGUISHING MEDIA: Foam, dry chemical CO 2 OSHA FLAMMABILITY CLASSIFICATION: Combustible liquid, Class III A SPECIAL FIRE FIGHTING PROCEDURES: Decomposition and/or products of combustion</pre>					
may be toxic. Use self con UNUSUAL FIRE AND EXPLOSION HAZ be toxic.					products may
SECTI	ION 5: RE	ACTIVITY DA	ATA		
<pre>STABILITY: Normally Stable CONDITIONS TO AVOID: Elevated temperatures. INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents, strong acids, strong bases. Mixing large quantities (1 gallon) with amines or epoxy hardeners can cause heat build-up and hazardous reaction.</pre>					

SECTION 5: REACTIVITY DATA (CON'T)

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide, Phenolic Derivatives.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Exposure to vapors at elevated temperatures may cause irritation to respiratory tract and difficulty breathing.
EYE: May cause irritation to the eyes.
SKIN: A single exposure to the skin is unlikely to result in harm.
SKIN ABSORPTION: Repeated exposure to the skin can cause sensitization.

INGESTION: Oral toxicity is low. No hazards expected from normal industrial exposure.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY:

NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Allergy, Eczema, or skin

conditions. EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush at once with potable water for at least 15 minutes.

- SKIN: Wash with soap and warm water. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes.
- **INGESTION:** Not likely to occur in normal handling. Give large quantities of water and get medical attention.

INHALATION: Remove to fresh air. Administer oxygen if breathing is difficult.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

- **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Avoid contact. Soak up with clay or other absorbent material. Place in covered container for disposal.
- **WASTE DISPOSAL METHOD:** Dispose in an approved incinerator or an approved landfill.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid contact.

OTHER PRECAUTIONS: Keep containers tightly closed when not in use. If mixture of A and B are allowed to remain in the mixing vessel past the pot life deadline, heat and a strong reaction will result.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Avoid breathing vapor mist or spray.

VENTILATION: Use with good ventilation.

PROTECTIVE GLOVES: Wear impervious gloves.

EYE PROTECTION: Wear splash-proof chemical goggles.

- **OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Provide eye fountain and safety shower.
- **WORK/HYGIENIC PRACTICES:** Practice good industrial hygiene. Wash with soap and water before eating, smoking, or using the restroom.

SECTION 9: REGULATORY INFORMATION

SARA TITLE III SECTION 313: Unless shown below, this product does not contain chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

CAS #	Chemical Name	Percent by Weight
106-89-8	Epichlorohydrin	trace

PROP 65 (CARCINOGEN): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer.

CAS #	Chemical Name	Percent by Weight
	None	

PROP 65 (TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight

PROP 65 (CARCINOGENIC & TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight None

- **HAZARDOUS WASTE INFORMATION:** Unless shown below, this product is not a hazardous waste according to definitions found in CFR-40.
- **STATE OF MICHIGAN CRITICAL MATERIALS:** Unless shown below, this product does not contain ingredients appearing on the State of Michigan Critical Materials List.

CAS # Chemical Name Percent by Weight None

D.O.T. PROPER SHIPPING NAME: Synthetic Resin Liquid PROPER SHIPPING NAME: Synthetic Resin Liquid HAZARD CLASS: non-hazardous UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Epoxy.com Product #206 COLD CURE BINDER PART A HMIS CODES: Н FRP **PRODUCT CODE:** #206 A 1 0 B 1 SECTION 1: MANUFACTURER IDENTIFICATION MANUFACTURER'S NAME: Epoxy Systems, Inc. 20774 W. Pennsylvania Ave. ADDRESS: Dunnellon, FL 34431 EMERGENCY NUMBER: 1-800-633-8253 DATE PRINTED: 6/2010 INFORMATION NUMBER: 1-352-489-1666 PREPARER: N. Lambert SECTION 2: HAZARDOUS INGREDIENTS ACGIH HAZARDOUS COMPONENTS CAS NUMBER OSHA PEL TLV WT % CARCINOGEN Resin 25068-38-6 NE NE 65-80 NΟ Alkyl Phenol 84852-15-3 NE NE 5 - 10NO Hexylene Glycol 107-41-5 NE 25 ppm 10-15 NO Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200. NE - Not Established SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS BOILING RANGE Above 400° F VAPOR DENSITY Approx. 3.5 (Air = 1) VAPOR PRESSURE Less than 1 mm Hg @ 100° F voc 0.00 SOLUBILITY IN WATER Very slight APPEARANCE AND ODOR Low viscosity clear liquid with a mild, pleasant aroma SPECIFIC GRAVITY (H20=1) 1.11 SECTION 4: FIRE AND EXPLOSION HAZARD DATA FLASH POINT: >200° F METHOD USED: Closed Cup FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: Not determined **UPPER:** Not determined EXTINGUISHING MEDIA: Foam, dry chemical CO 2 OSHA FLAMMABILITY CLASSIFICATION: Combustible liquid, Class III A SPECIAL FIRE FIGHTING PROCEDURES: Decomposition and/or products of combustion may be toxic. Use self contained breathing equipment. **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Decomposition and combustion products may be toxic. SECTION 5: REACTIVITY DATA **STABILITY:** Normally Stable CONDITIONS TO AVOID: Elevated temperatures. **INCOMPATIBILITY (MATERIALS TO AVOID):** Avoid contact with strong oxidizing agents, strong acids, strong bases. Mixing large quantities (1 gallon) with amines or epoxy hardeners can cause heat build-up and hazardous reaction. HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide, Phenolic Derivatives. HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Exposure to vapors at elevated temperatures may cause irritation to respiratory tract and difficulty breathing. EYE: May cause irritation to the eyes.

SKIN: A single exposure to the skin is unlikely to result in harm.

SKIN ABSORPTION: Repeated exposure to the skin can cause sensitization. INGESTION: Oral toxicity is low. No hazards expected from normal industrial exposure.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY:

NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Allergy, Eczema, or skin conditions.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush at once with potable water for at least 15 minutes.

SKIN: Wash with soap and warm water. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes.

INGESTION: Not likely to occur in normal handling. Give large quantities of water and get medical attention.

INHALATION: Remove to fresh air. Administer oxygen if breathing is difficult.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

- **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Avoid contact. Soak up with clay or other absorbent material. Place in covered container for disposal.
- **WASTE DISPOSAL METHOD:** Dispose in an approved incinerator or an approved landfill.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid contact.

OTHER PRECAUTIONS: Keep containers tightly closed when not in use. If mixture of A and B are allowed to remain in the mixing vessel past the pot life deadline, heat and a strong reaction will result. Grinding or other abrasive action to cured film may develop Micro crystalline Silica dust. Wear a dust mask during such operations.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Avoid breathing vapor mist or spray. **VENTILATION:** Use with good ventilation.

PROTECTIVE GLOVES: Wear impervious gloves.

EYE PROTECTION: Wear splash-proof chemical goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Provide eye fountain and safety shower.

WORK/HYGIENIC PRACTICES: Wash hands thoroughly after use, before eating or smoking. Store in a cool, dry area.

SECTION 9: REGULATORY INFORMATION

SARA TITLE III SECTION 313: Unless shown below, this product does not contain the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

CAS # Chemical Name Percent by Weight None

PROP 65 (CARCINOGEN): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer.

CAS #	Chemical Name	Percent by Weight
	None	

PROP 65 (TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight

PROP 65 (CARCINOGENIC & TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight None

HAZARDOUS WASTE INFORMATION: Unless shown below, this product is not a hazardous waste according to definitions found in CFR-40.

STATE OF MICHIGAN CRITICAL MATERIALS: Unless shown below, this product does not contain ingredients appearing on the State of Michigan Critical Materials List.

CAS # Chemical Name Percent by Weight None

D.O.T. PROPER SHIPPING NAME: Synthetic Resin Liquid PROPER SHIPPING NAME: Synthetic Resin Liquid HAZARD CLASS: non-hazardous UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Epoxy.com Produ	ct #204 COLD	CURE COAT	ING PART	A HMIS
CODES:				Н	FRP
PRODUCT CODE:	204A				
				1	1 0 B
	SECTION 1:	MANUFACTUR	ER IDENTI	FICATION	
MANUFACTURER 'S	NAME: Epoxy	Systems, Ind	с.		
ADDRESS:	20774	W. Pennsylva	ania Ave.		
	Dunne	llon, FL 344	431		
EMERGENCY NUMB	ER: 1-800-63	3-8253	DATE PRIN	ITED: 06/	2010

SECTION 2: HAZARDOUS INGREDIENTS

PREPARER:

N. Lambert

			ACGIH		
HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	TLV	WT %	CARCINOGEN
Resin	25068-38-6	NE	NE	45-65	NO
Benzyl Alcohol	100-51-6	NE	NE	5-15	NO
Talc	14807-96-6	2 mg/m³	2 mg/m³	10-30	NO
Depending on color, one or	more of the	following m	ay be pre	esent:	
Titanium Dioxide	13463-67-7		10 mg/m ³	° 1-5	NO
Black Iron Oxide	1317-61-9	10 ppm	10 mg/m^3	³ <1	NO
Red Iron Oxide	1332-37-2	10 ppm	10 mg/m^3	³ 1 − 5	NO
Yellow Iron Oxide	51274-00-1	10 ppm	5 mg/m³	³ <1	NO
Chromium Oxide	1308-38-9	.5 mg/m³	.5 mg/m³	<1	

The exposure limits shown above for pigments are for dust exposure. They are not known to be hazardous after blended into a liquid. Wet sanding is suggested to eliminate airborne dust, if product is machined or ground. The only other exposure limits established for ingredients of this product apply to nuisance dusts from inert fillers. These fillers are blended into a liquid and pose no hazard as supplied.

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

NE - Not Established

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE	Not determined
VAPOR DENSITY	Not determined
VAPOR PRESSURE	1 mm Hg @ 200° F
VOC	0.00
SOLUBILITY IN WATER	NIL
APPEARANCE AND ODOR	Moderately viscous pigmented liquid with a mild odor
SPECIFIC GRAVITY (H20=1)	1.51

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200° F

METHOD USED: Closed Cup

INFORMATION NUMBER: 1-352-489-1666

FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: Not determined UPPER: Not determined EXTINGUISHING MEDIA: Foam, dry chemical CO 2 OSHA FLAMMABILITY CLASSIFICATION: Combustible liquid, Class III A

SECTION 4: FIRE AND EXPLOSION HAZARD DATA (CON'T)

SPECIAL FIRE FIGHTING PROCEDURES: Decomposition and/or products of combustion may be toxic. Use self contained breathing equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Decomposition and combustion products may be toxic.

SECTION 5: REACTIVITY DATA

STABILITY: Normally Stable

CONDITIONS TO AVOID: Elevated temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents, strong acids, strong bases. Mixing large quantities (1 gallon) with amines or epoxy hardeners can cause heat build-up and hazardous reaction.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide, Phenolic Derivatives.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Exposure to vapors at elevated temperatures may cause irritation to respiratory tract and difficulty breathing.

EYE: May cause irritation to the eyes.

SKIN: A single exposure to the skin is unlikely to result in harm. SKIN ABSORPTION: Repeated exposure to the skin can cause sensitization. INGESTION: Oral toxicity is low. No hazards expected from normal

industrial exposure.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY:

NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Allergy, Eczema, or skin conditions.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush at once with potable water for at least 15 minutes.

SKIN: Wash with soap and warm water. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes.

INGESTION: Not likely to occur in normal handling. Give large quantities of water and get medical attention.

INHALATION: Remove to fresh air. Administer oxygen if breathing is difficult.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid contact. Soak up with clay or other absorbent material. Place in covered container for disposal.

WASTE DISPOSAL METHOD: Dispose in an approved incinerator or an approved landfill.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid contact.

OTHER PRECAUTIONS: Keep containers tightly closed when not in use. If mixture of A and B are allowed to remain in the mixing vessel past the pot life deadline, heat and a strong reaction will result. Grinding or other abrasive action to cured film may develop Micro crystalline Silica dust. Wear a dust mask during such operations.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Avoid breathing vapor mist or spray. **VENTILATION:** Use with good ventilation.

PROTECTIVE GLOVES: Wear impervious gloves.

EYE PROTECTION: Wear splash-proof chemical goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Provide eye fountain and safety shower.

WORK/HYGIENIC PRACTICES: Practice good industrial hygiene. Wash with soap and water before eating, smoking, or using the restroom.

SECTION 9: REGULATORY INFORMATION

SARA TITLE III SECTION 313: Unless shown below, this product does not contain the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

CAS #

1308-38-9

Chemical Name Percent by Weight Chromium compound

<1% (not in all formulations)

PROP 65 (CARCINOGEN): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer.

	CZ	AS #	Chemical Name	Pe	rcent by	Weight
			None			
ΔĐ	65		Unloga shown hold	u this product	doog not	aontain

PROP 65 (TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause birth defects or other reproductive harm.

CAS #

Chemical Name None

PROP 65 (CARCINOGENIC & TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

CAS

Chemical Name None

Percent by Weight

Percent by Weight

HAZARDOUS WASTE INFORMATION: Unless shown below, this product is not a hazardous waste according to definitions found in CFR-40.

STATE OF MICHIGAN CRITICAL MATERIALS: Unless shown below, this product does not contain ingredients appearing on the State of Michigan Critical Materials List.

CAS # Chemical Name Percent by Weight None D.O.T. PROPER SHIPPING NAME: Synthetic Resin Liquid

PROPER SHIPPING NAME: Synthetic Resin Liquid non-hazardous HAZARD CLASS: UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Epoxy.	com Polymeric COLD	CURE HARDENER	PART B	HMIS	
CODES:			Н	FRP	
PRODUCT CODE: ESI #	203/#204/#206 -B				
			3	1 0 C	
SECTION 1: MANUFACTURER IDENTIFICATION					
MANUFACTURER'S NAME:	Epoxy Systems,	Inc.			
ADDRESS:	20774 W. Pennsy	lvania Ave.			
	Dunnellon, FL	34431			
EMERGENCY NUMBER:	1-800-633-8253	DATE PRINTE	D: 6/2010		
INFORMATION NUMBER:	1-352-489-1666	PREPARER:	N. Lambert		

SECTION 2: HAZARDOUS INGREDIENTS

		OSHA	ACGIH		
HAZARDOUS COMPONENTS	CAS NUMBER	PEL	TLV	WT %	CARCINOGEN
Benzene-1, 3-Dimethanamine	1447-55-0	NE	NE	10-20	NO
Trimethylhexamethylenediamine	3236-53-1	NE	NE	10-20	NO
Paratertiarybutylphenol	98-54-4	NE	NE	30-40	NO
Benzyl Alcohol	100-51-6	NE	NE	1-10	NO
Alkyl Phenol	84852-15-3	NE	NE	20-30	NO

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910-1200.

NE - Not Established

SECTION 3: PHYSIC	CAL/CHEMICAL CHARACTERISTICS
BOILING POINT	>390° F
VAPOR DENSITY	NE
VAPOR PRESSURE	Approx. 1mm Hg @ 200° F
VOC	0.00
SOLUBILITY IN WATER	Partial
APPEARANCE	Low viscosity with sharp ammonia
	odor
SPECIFIC GRAVITY (H20=1)	0.99
EVAPORATION RATE	NE

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200° F

METHOD USED: Closed Cup

FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: Not determined UPPER: Not determined

SR: Not determined

EXTINGUISHING MEDIA: Foam, dry chemical, CO2
OSHA FLAMMABILITY CLASSIFICATION: Combustible liquid, Class III B
SPECIAL FIRE FIGHTING PROCEDURES: Wear positive pressure self contained
breathing equipment. Use water to cool containers exposed to fire.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Toxic fumes present when this material
involved in fire. Containers may rupture.

SECTION 5: REACTIVITY DATA

STABILITY: Normally Stable.

CONDITIONS TO AVOID: Contact with acids such as Hydrochloric or Sulfuric. INCOMPATIBILITY (MATERIALS TO AVOID): Avoid strong oxidizing agents and epoxy resins under uncontrolled conditions.

SECTION 5: REACTIVITY DATA (CON'T)

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: When exposed to fire, oxides of Carbon and Nitrogen will be generated.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Vapors can cause severe irritation of respiratory tract. SKIN: Corrosive - Can cause burns to skin.

EYE: Vapors - Can cause irritation and burns to eyes.

INGESTION: Can cause severe damage to mouth and throat.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY:

NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Skin contact may aggrevate existing dermatitis (skin condition). Over exposure to vapor or mist may aggrevate existing respiratory conditions such as asthma,

bronchitis, or fibrotic respiratory disease.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush immediately for 15 minutes with large amounts of potable water. <u>DO NOT</u> attempt to neutralize with chemical agents. Get immediate medical attention.

SKIN: Flush immediately for 15 minutes with potable water. <u>DO NOT</u> attempt to neutralize with chemical agents. Remove contaminated clothing. Launder before reuse. Discard contaminated shoes. Get medical attention if swelling and/or irritation occurs.

INGESTION: Give water to dilute stomach contents. <u>DO NOT</u> induce vomiting. If vomiting occurs, give fluids again. Get immediate medical attention.

- Do not give anything by mouth to an unconscious or convulsing person. INHALATION: Remove to fresh air. Get medical attention if effects persist.
- **OTHER INSTRUCTIONS:** Swallowing this corrosive material may result in severe ulceration, inflamation, and possible perforation of the upper alimentary tract, with hemorrhage and fluid loss. Aspiration of this product during induced emesis can result in severe lung injury. If evacuation of stomach is necessary, use method least likely to cause aspiration, such as gastric lavage after endotracheal intubation. Contact a Poison Control Center for additional treatment information.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

- STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid contact. Allow only personnel wearing goggles, neoprene or rubber gloves and protective clothing to clean up spill. In confined areas a full face respirator is recommended. Absorb spill with clay, diatomaceous earth or other absorbent material. Place in disposal containers.
- **WASTE DISPOSAL METHOD:** Dispose of in approved incinerator or an approved landfill.
- PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid contact. Keep containers tightly closed when not in use. Do not remove labels from empty containers. If mixtures of Part B and Part A are allowed to remain in the mixing container past the pot life deadline, heat and a strong reaction will result.

OTHER PRECAUTIONS: none

SECTION 8: CONTROL MEASURES **RESPIRATORY PROTECTION:** If vapor or mist is generated and the occupational exposure limit is exceeded, use appropriate NIOSH/MSHA approved self contained breathing equipment or a full face respirator. **VENTILATION:** Mechanical ventilation required if TLV is expected to be exceeded in confined areas. **PROTECTIVE GLOVES:** Neoprene or natural rubber gloves EYE PROTECTION: Chemical goggles OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Body covering clothes WORK/HYGIENIC PRACTICES: Practice good industrial hygiene. Wash with soap and water before eating, smoking, or using the restroom. SECTION 9: REGULATORY INFORMATION SARA TITLE III SECTION 313: Unless shown below, this product does not contain chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372: CAS # Chemical Name Percent by Weight None **PROP 65 (CARCINOGEN):** Unless shown below, this product does not contain chemicals known to the state of California to cause cancer. CAS # Chemical Name Percent by Weight None PROP 65 (TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause birth defects or other reproductive harm. CAS # Chemical Name Percent by Weight None PROP 65 (CARCINOGENIC & TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer or birth defects or other reproductive harm. CAS # Chemical Name Percent by Weight None HAZARDOUS WASTE INFORMATION: Unless shown below, this product is not a hazardous waste according to definitions found in CFR-40. STATE OF MICHIGAN CRITICAL MATERIALS: Unless shown below, this product does not contain ingredients appearing on the State of Michigan Critical Materials List. CAS # Chemical Name Percent by Weight None D. O. T. PROPER SHIPPING NAME: Caustic Alkali Liquid, N.O.S. (Aliphatic Amines); 8; UN1719; PG II PROPER SHIPPING NAME: Caustic Alkali Liquid, N.O.S. (Aliphatic Amines) Class 8, Corrosive HAZARD CLASS: UN/NA ID NUMBER: UN 1719 PACKING GROUP: ΙI SECTION 10: DISCLAIMER Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.