461 High Solids Urethane Topcoat - Clear

Part A







Printed: 11/09/2015 Revision: 11/09/2015

Page: 1

1. Product and Company Identification

Product Code: 461-CLEAR

Product Name: 461 High Solids Urethane Topcoat - Clear Part A

Trade Name: 461 High Solids Urethane Topcoat - Clear Part A

Manufacturer Information

Company Name: Epoxy Systems, Inc.

20774 W Pennsylvania Ave Dunnellon, Florida 34431

Phone Number: +1 (352) 489-1666

Emergency Contact: PERS (USA) (800) 633-8253

Alternate Emergency Contact: PERS (International) +1 (801) 629-0667

Industrial Maintenance Coatings

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Acute Toxicity: Inhalation, Category 4	Exclamation point	Warning	Harmful if inhaled
Respiratory Sensitization, Category 1	Health hazard	Danger	May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin Sensitization, Category 1	Exclamation point	Warning	May cause an allergic skin reaction

GHS Hazard Phrases

- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H373 May cause damage to lungs through prolonged or repeated exposure.

GHS Precaution Phrases

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P285 In case of inadequate ventilation wear respiratory protection.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases

P304+341 - IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

P342+311 - If experiencing respiratory symptoms call a POISON CENTER or doctor/physician.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P315 - Get immediate medical advice/attention.

461 High Solids Urethane Topcoat - Clear

Part A

Printed: 11/09/2015 Revision: 11/09/2015

Page:

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to local, state, and federal authority requirements.

P402 - Store in a dry place.

Potential Health Effects (Acute and Chronic)

May cause slight skin irritation or skin sensitization. May be slightly irritating to eyes and respiratory system.

Inhalation

May cause respiratory irritation. May cause allergic respiratory reaction.

Skin Contact

May cause skin irritation. May cause allergic skin reaction.

Eve Contact

May cause eye irritation.

Ingestion

May be harmful if swallowed.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)

CAS# Concentration

1. Poly(hexamethylene diisocyanate)

28182-81-2 >=99 %

4. First Aid Measures

Emergency and First Aid Procedures

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use first aid treatment according to the nature of the injury.

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Signs and Symptoms Of Exposure

Mild irritation effect. May cause allergic skin reaction. If material is heated, sprayed, vapors from this material can produce asthmatic sensitization to the respiratory system.

5. Fire Fighting Measures

Flash Pt: > 300.00 F Method Used: Closed Cup

LEL: NE **Explosive Limits:** UEL: NE

Autoignition Pt: No data available.

461 High Solids Urethane Topcoat - Clear Part A

Printed: 11/09/2015 Revision: 11/09/2015

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Closed container may rupture (due to build up in pressure) when exposed to extreme heat.

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Oxides of nitrogen, Traces of hydrogen cyanide, Isocyanate vapors

Suitable Extinguishing Media

Dry extinguishing media, foam.

Unsuitable Extinguishing Media

Reacts with water, with formation of carbon dioxide.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and Storage

Hazard Label Information:

Avoid contact with skin and eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on clothing.

Precautions To Be Taken in Storing

Store away from incompatible material. Store in cool/well-ventilated place.

Other Precautions

Wash thoroughly after handling.

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name) CAS# **OSHA PEL ACGIH TLV** Other Limits 1. Poly(hexamethylene diisocyanate) 28182-81-2 No data. No data. No data.

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Respiratory protection in case of vapor/aerosol release. Combination filter for gases/vapors of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2). In isocyanate-containing environments (air-purifying or fresh air-supplied) may be necessary for spray applications or other situations such as high temperature use which may produce inhalation exposures.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene are recommended.

461 High Solids Urethane Topcoat - Clear Part A

Page: 4 Printed: 11/09/2015 Revision: 11/09/2015

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways. May be hazardous to the environment if released in large quantities.

9. Physical and Chemical Properties					
Physical States:	[] Gas [X] Liquid [] Solid				
Melting Point:	NE				
Boiling Point:	NE				
Decomposition Temperature:	NE				
Autoignition Pt:	No data.				
Flash Pt:	> 300.00 F Method Used: Closed Cup				
Explosive Limits:	LEL: NE UEL: NE				
Specific Gravity (Water = 1):	~ 1.17				
Density:	~ 9.76 LB/GL				
Vapor Pressure (vs. Air or mm Hg):	NE				
Vapor Density (vs. Air = 1):	NE				
Evaporation Rate:	NE				
Solubility in Water:	NP				
Percent Volatile:	N.A.				
VOC / Volume:	NP				
HAP / Volume:	NP				
Saturated Vapor Concentration:	NE				
Appearance and Odor					
Odor: Mild.					
Appearance: Clear.					
	10. Stability and Reactivity				
Stability:	Unstable [] Stable [X]				
Reactivity					
Reacts with alcohols, amines. Reacts with water, with formation of carbon dioxide.					
Conditions To Avoid - Instability					
Extreme temperatures.					
Incompatibility - Materials To Avoid Reacts with alcohols amines Rea	acts with water with formation of carbon diovide				
Reacts with alcohols, amines. Reacts with water, with formation of carbon dioxide. Hazardous Decomposition Or Byproducts					
Carbon monoxide, Oxides of nitrogen, Traces of hydrogen cyanide, Isocyanate vapors					
Possibility of Hazardous Polymerization:	Will occur [] Will not occur [X]				

461 High Solids Urethane Topcoat - Clear Part A

Printed: 11/09/2015 Revision: 11/09/2015

Conditions To Avoid - Hazardous Reactions

Extreme temperatures. Will not undergo hazardous polymerization in normal storage conditions.

11. Toxicological Information

Toxicological Information

May cause sensitization by inhalation. May cause sensitization by skin contact.

Chronic Toxicological Effects

Respiratory or skin sensitization.

Irritation or Corrosion

May cause slight skin irritation or skin sensitization. May be slightly irritating to eyes and respiratory system.

Symptoms related to Toxicological Characteristics

May cause respiratory sensitization. May cause allergic reaction leading to asthma-like spasms of the bronchial tubes and difficulty in breathing. Persons with asthmatic conditions, chronic bronchitis, other chronic respiratory diseases, recurrent eczema or pulmonary sensitization should be excluded from working with isocyanates. Once a person is diagnosed as having pulmonary sensitization (allergic asthma) to isocyanates, further exposure is not recommended.

Hazardous Components (Chemical Name)	CAS#	NTP	IARC	ACGIH	OSHA
Poly(hexamethylene diisocyanate)	28182-81-2	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information

Avoid release to the environment.

Results of PBT and vPvB assessment

No data available.

Persistence and Degradability

Not readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

not reported, unknown.

13. Disposal Considerations

Waste Disposal Method

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name Not Regulated.

AIR TRANSPORT (ICAO/IATA)

ICAO/IATA Shipping Name Not Regulated.

MARINE TRANSPORT (IMDG/IMO)

IMDG/IMO Shipping Name Not Regulated.

Marine Pollutant: No

15. Regulatory Information

US EPA SARA Title III

Ha	azardous Components (Chemical Name)	CAS#	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1	Poly(hexamethylene diisocyanate)	28182-81-2	No	No	No	No

461 High Solids Urethane Topcoat - Clear Part A

Printed: 11/09/2015 Revision: 11/09/2015

Page: 6

Regulatory Information

SARA Section 311/312: Acute, Chronic Health Hazard.

16. Other Information

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however Epoxy Systems, Inc. makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.

Revision Date: 11/09/2015