, Special Hazard

Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B



Printed: 06/12/2015 Revision: 06/12/2015

1. Product and Company Identification						
Product Code:	633-B					
Product Name:	633 Epoxy Novolac Coating Ha	ardener - Part B				
Trade Name:	Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B					
Manufacturer Information						
Company Name:	Epoxy Systems, Inc.					
	20774 W. Pennsylvania Ave.					
	Dunnellon, FL 34431					
Phone Number:	352-489-1666					
Emergency Contact:	PERS (USA)	(800)633-8253				
Alternate Emergency Contact:	PERS (International)	801-629-0667				
Intended Use:	Industrial floor coatings.					

# 2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Skin Sensitization, Category 1A	Exclamation	Warning	May cause an allergic skin reaction
	point		
Skin Corrosion/Irritation, Category 1B	Corrosive	Danger	Causes severe skin burns and eye damage
Serious Eye Damage/Eye Irritation, Category 1	Corrosive	Danger	Causes serious eye damage
Acute Toxicity: Oral, Category 4	Exclamation	Warning	Harmful if swallowed
	point		
Toxic To Reproduction, Category 2	Health hazard	Warning	Suspected of damaging fertility or the unborn child
Aquatic Toxicity (Acute), Category 1	Pollution	Warning	Very toxic to aquatic life
Aquatic Toxicity (Chronic), Category 1	Pollution	Warning	Very toxic to aquatic life with long lasting effects

#### **GHS Hazard Phrases**

- H317 May cause an allergic skin reaction.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H302 Harmful if swallowed.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

# **GHS Precaution Phrases**

- P261 Avoid breathing dust/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P362+364 Take off contaminated clothing and wash it before reuse.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.
- P273 Avoid release to the environment.

# **GHS Response Phrases**

P361 - Remove/Take off immediately all contaminated clothing.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B

Page: 2 Printed: 06/12/2015 Revision: 06/12/2015

and easy to do. Continue rinsing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313 - Get medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 - Get medical attention/advice if you feel unwell.

P308+313 - IF exposed or concerned: Get medical attention/advice.

P391 - Collect spillage.

# **GHS Storage and Disposal Phrases**

P501 - Dispose of contents/container to local, state, and federal authority requirements.

# **Potential Health Effects (Acute and Chronic)**

Corrosive! Damages skin and eyes.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

#### Inhalation

May cause respiratory irritation.

# **Skin Contact**

Causes severe skin irritation. Causes skin burns.

#### **Eye Contact**

Corrosive/irritation to eyes. Causes eye burns.

#### Ingestion

Harmful if swallowed.

#### **Recommended Exposure Limits**

Not established.

# Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

# **OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

# 3. Composition/Information on Ingredients

На	zardous Components (Chemical Name)	CAS #	Concentration
1.	Benzenemethanol	100-51-6	25 - 35 %
2.	Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	25 - 35%
3.	Phenol, 4-nonyl-, branched	84852-15-3	10 - 20%
4.	Aliphatic Amine	NA	1.0 - 5.0%
5.	Diethylenetriamine	111-40-0	1.0 - 5.0%
6.	Cyclohexylamine, 4,4'-methylenebis-	1761-71-3	1.0 - 5.0%
7.	Organic Acid	NA	1.0 - 5.0%
8.	4,4'-Isopropylidenediphenol	80-05-7	1.0 - 5.0%
9.	2,4,6-Tris(Dimethylaminomethyl)Phenol	90-72-2	1.0 - 5.0%

# 4. First Aid Measures

# **Emergency and First Aid Procedures**

# In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

# In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

# Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B

# In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention immediately.

# In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately.

# Signs and Symptoms Of Exposure

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

	5. Fire Fighting Measures				
Flash Pt:	> 200.00 F Method Used: Pensky-Marten Closed Cup				
Explosive Limits:	LEL: NE UEL: NE				
Autoignition Pt:	No data available.				

# **Fire Fighting Instructions**

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

# Flammable Properties and Hazards

Combustible material: may burn but does not ignite readily.

# **Hazardous Combustion Products**

In a fire, product may produce the following: Carbon monoxide, Aldehydes. Carbon dioxide, Nitrogen oxides, Fire may produce irritating, corrosive and/or toxic gases.

# **Suitable Extinguishing Media**

CO2, dry chemical, dry sand, alcohol-resistant foam.

# **Unsuitable Extinguishing Media**

Do not use a direct water stream, which may spread fire.

# 6. Accidental Release Measures

# Steps To Be Taken In Case Material Is Released Or Spilled

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

# Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

# **Environmental Precautions**

Prevent entry into waterways, sewers, basements or confined areas.

# 7. Handling and Storage

# Hazard Label Information:

Avoid contact with eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

# **Precautions To Be Taken in Handling**

Provide adequate ventilation. Wear all personal protection required in section 8.

### Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible material.

#### **Other Precautions**

Wash thoroughly after handling.

	8. Exposure Controls/Personal Protection							
На	zardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits			
1.	Benzenemethanol	100-51-6	No data.	No data.	No data.			
2.	Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	No data.	No data.	No data.			
3.	Phenol, 4-nonyl-, branched	84852-15-3	No data.	No data.	No data.			
4.	Aliphatic Amine	NA	No data.	No data.	No data.			
5.	Diethylenetriamine	111-40-0	No data.	1 ppm	No data.			
6.	Cyclohexylamine, 4,4'-methylenebis-	1761-71-3	No data.	No data.	No data.			
7.	Organic Acid	NA	No data.	No data.	No data.			
8.	4,4'-Isopropylidenediphenol	80-05-7	No data.	No data.	No data.			
9.	2,4,6-Tris(Dimethylaminomethyl)Phenol	90-72-2	No data.	No data.	No data.			

#### **Protective Equipment Summary - Hazard Label Information:**

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

#### **Respiratory Equipment (Specify Type)**

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### **Eye Protection**

Safety glasses, or goggles.

#### **Protective Gloves**

Nitrile rubber and Neoprene are recommended.

#### **Other Protective Clothing**

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

#### **Engineering Controls (Ventilation etc.)**

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

#### Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

### **Environmental Exposure Controls**

Avoid runoff into storm sewers and ditches which lead to waterways.

9. Physical and Chemical Properties							
Physical States:	[]Gas	[ X ] Liquid	[ ] Solid				
Melting Point:	NE						
Boiling Point:	NE						
Decomposition Temperature:	NE						
Autoignition Pt:	No data.						

# Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B

Flash Pt:	> 200.00 F Method Used: Pensky-Marten Closed Cup						
Explosive Limits:	LEL: NE UEL: NE						
Specific Gravity (Water = 1):	~ 1.019						
Density:	~ 8.5 LB/GL						
Vapor Pressure (vs. Air or mm Hg):	NE						
Vapor Density (vs. Air = 1):	NE						
Evaporation Rate:	NE						
Solubility in Water:	No data.						
Percent Volatile:	N.A.						
VOC / Volume:	NP						
HAP / Volume:	NP						
Saturated Vapor Concentration:	NE						
Appearance and Odor							
Odor: amine-like.							
Appearance: Liquid. amber.							
	10. Stability and Reactivity						
Stability:	Unstable [ ] Stable [ X ]						
Reactivity							
Avoid: acids, Avoid uncontrolled	d contact with isocyanates. Avoid: Uncontrolled reactions with epoxies.						
Conditions To Avoid - Instability							
Extreme temperatures.							
Incompatibility - Materials To Avoid							
	gents. Nitrous acid and other nitrosating agents.						
Hazardous Decomposition Or Bypro							
Thermal decomposition may pro-	duca smoka, carbon monovida, carbon diovida, aldahudas, ammonia Ni						

Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, aldehydes. ammonia. Nitric Acids. Nitrogen oxides.

Possibility of Hazardous Will occur [ ] Will not occur [ X ]

# **Polymerization:**

#### **Conditions To Avoid - Hazardous Reactions**

Will not undergo hazardous polymerization in normal storage conditions.

# **11. Toxicological Information**

#### **Toxicological Information**

May cause sensitization by skin contact.

# **Chronic Toxicological Effects**

Skin sensitization.

# **Irritation or Corrosion**

Corrosive! Damages skin and eyes.

# Symptoms related to Toxicological Characteristics

May cause sensitization by skin contact. May cause skin irritation or burns.

Can cause eye irritation or burns.

Ha	azardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1.	Benzenemethanol	100-51-6	n.a.	n.a.	n.a.	n.a.
2.	Formaldehyde, polymer with benzenamine,	135108-88-2	n.a.	n.a.	n.a.	n.a.
	hydrogenated					

Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B

Page: 6 Printed: 06/12/2015 Revision: 06/12/2015

Ha	azardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
3.	Phenol, 4-nonyl-, branched	84852-15-3	n.a.	n.a.	n.a.	n.a.
4.	Aliphatic Amine	NA	n.a.	n.a.	n.a.	n.a.
5.	Diethylenetriamine	111-40-0	n.a.	n.a.	n.a.	n.a.
6.	Cyclohexylamine, 4,4'-methylenebis-	1761-71-3	n.a.	n.a.	n.a.	n.a.
7.	Organic Acid	NA	n.a.	n.a.	n.a.	n.a.
8.	4,4'-Isopropylidenediphenol	80-05-7	n.a.	n.a.	n.a.	n.a.
9.	2,4,6-Tris(Dimethylaminomethyl)Phenol	90-72-2	n.a.	n.a.	n.a.	n.a.

# **12. Ecological Information**

#### **General Ecological Information**

Avoid release to the environment. Do not empty into drains. May be hazardous to the environment if released in large quantities.

#### Results of PBT and vPvB assessment

No data available.

# Persistence and Degradability

Not readily biodegradable.

#### **Bioaccumulative Potential**

No data available.

## **Mobility in Soil**

not reported, unknown.

# **13. Disposal Considerations**

#### Waste Disposal Method

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

. . .

\_

	14. Transport Information
LAND TRANSPORT (US DOT)	
DOT Proper Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Contains Aliphatic Amines, Nonylphenol) MARINE POLLUTANT.
	Marine Pollutant(s): Nonylphenol.
	NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.
DOT Hazard Class:	8
DOT Hazard Label:	CORROSIVE
UN/NA Number:	UN1719
Packing Group:	III
Precautionary Label	Corrosive! Damages skin and eyes. May cause sensitization by skin contact. May be harmful if swallowed.
AIR TRANSPORT (ICAO/IATA)	
ICAO/IATA Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Contains Aliphatic Amines, Nonylphenol) MARINE POLLUTANT.
	Marine Pollutant(s): Nonylphenol.
	NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or

Epoxy.com 633 Epoxy Novolac Coating Hardener - Part B

aircraft.

Marine Pollutant:	Yes
IMDG EMS Number:	FA,SB
Packing Group:	III
Hazard Class:	8 - CORROSIVE
UN Number:	1719
	Marine Pollutant(s): Nonylphenol.
IMDG/IMO Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Contains Aliphatic Amines, Nonylphenol) MARINE POLLUTANT.
MARINE TRANSPORT (IMDG/IMO)	
•	
Packing Group:	
Hazard Class:	8 - CORROSIVE
UN Number:	1719

# **15. Regulatory Information**

U U	JS EPA SARA Title III					
н	azardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1.	Benzenemethanol	100-51-6	No	No	No	No
2.	Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	No	No	No	No
3.	Phenol, 4-nonyl-, branched	84852-15-3	No	No	No	No
4.	Aliphatic Amine	NA	No	No	No	No
5.	Diethylenetriamine	111-40-0	No	No	No	No
6.	Cyclohexylamine, 4,4'-methylenebis-	1761-71-3	No	No	No	No
7.	Organic Acid	NA	No	No	No	No
8.	4,4'-Isopropylidenediphenol	80-05-7	No	No	Yes	No
9.	2,4,6-Tris(Dimethylaminomethyl)Phenol	90-72-2	No	No	No	No
	) a guilata nu Information					

#### **Regulatory Information**

SARA Section 311/312: Acute Health Hazard.

# **16. Other Information**

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP=NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

#### **Company Policy or Disclaimer**

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however Epoxy Systems, Inc. makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof. **Revision Date:** 06/12/2015