



SECTION 1: IDENTIFICATION

Company:	Epoxy Systems, Inc.
Address:	20774 West Pennsylvania Ave Dunnellon, FL 34431
Product Name:	B Component: Epoxy.com # 1
Product Description:	100% SOLIDS EPOXY PIGMENTED PART B
Emergency Contact No.:	1-800-633-8253 PERS
Date Prepared or Revised:	02/17/2015

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification	Placard	Key word	GHS hazard phrase
Skin Sensitization,	Category 1A Exclamation	Warning	May cause an allergic skin reaction point
Skin Corrosion/Irritation,	Category 1A Corrosive Danger	Causes	severe skin burns and eye damage
Serious Eye Damage/Eye Irritation,	Category 1 Corrosive	Danger	Causes serious eye damage
Acute Toxicity: Oral,	Category 4 Exclamation	Warning	Harmful if swallowed point

GHS Hazard Phrases

H317 - May cause an allergic skin reaction.
H314 - Causes severe skin burns and eye damage.
H302 - Harmful if swallowed.
H332 - Harmful if inhaled.
H312 - Harmful in contact with skin.

GHS Precaution Phrases

P281 - Use personal protective equipment as required.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

GHS Response Phrases

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P309+311 - Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to local, state, and federal authority requirements.

Potential Health Effects (Acute and Chronic)

May cause sensitization. May cause skin irritation or burns. May cause respiratory tract irritation.
May cause allergic skin reaction. Can cause severe eye irritation.

Inhalation

Corrosive to respiratory tract. May cause respiratory sensitization.

Skin Contact

Contact with substance may cause severe burns to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eye Contact

Corrosive/irritation to eyes. Causes eye burns.

Ingestion

Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Phenol, 4-nonyl-, branched	84852-15-3	40 - 60 %
2. *Poly(oxy(methyl-1,2-ethanediyl)	9046-10-0	30 - 45 %
3. 1,5-Pentanediamine, 2-methyl-	15520-10-2	1.0 - 10 %
4. 4-tert-Butylphenol	98-54-4	1.0 - 10 %
5. 1,3-Benzenedimethanamine	1477-55-0	1.0 - 10 %

SECTION 4: FIRST-AID MEASURES

Emergency and First Aid Procedures

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention immediately.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately.

Signs and Symptoms Of Exposure

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Pt: > 200.00 C Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data available.

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Combustible material: may burn but does not ignite readily.

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Fire may produce irritating, corrosive and/or toxic gases.

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use a direct water stream, which may spread fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES**Steps To Be Taken In Case Material Is Released Or Spilled**

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7: HANDLING AND STORAGE

Hazard Label Information:

Avoid contact with skin and eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Wear all personal protection required in section 8.

Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible material.

Other Precautions

Wash thoroughly after handling.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TWA	Other Limits
1. Phenol, 4-nonyl-, branched		84852-15-3	No data.	No data.
2. *Poly(oxy(methyl-1,2-ethanediyl)		9046-10-0	No data.	No data.
3. 1,5-Pentanediamine, 2-methyl-		15520-10-2	No data.	No data.
4. 4-tert-Butylphenol		98-54-4	No data.	No data.
5. 1,3-Benzenedimethanamine		1477-55-0	No data.	No data.

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene is recommended.

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

Melting Point: NE

Boiling Point: NE

Decomposition Temperature: NE

Autoignition Pt: No data.

Flash Pt: > 200.00 F Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Specific Gravity (Water = 1): ~ .9489

Density: ~ 7.914 LB/GL

Vapor Pressure (vs. Air or mm Hg): NE

Vapor Density (vs. Air = 1): NE

Evaporation Rate: NE

Solubility in Water: No

Percent Volatile: N.A.

VOC / Volume: NP

HAP / Volume: NP

Saturated Vapor Concentration: NE

Appearance and Odor

Odor: amine-like.

Appearance: Liquid. amber.

SECTION 10: STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Reactivity

Avoid: acids, alkalis, oxidizing agents.

Conditions To Avoid - Instability

Extreme temperatures.

Incompatibility - Materials To Avoid

Avoid strong acids, bases, and oxidizing agents. Avoid contact with amines.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, and phenolics.

Possibility of Hazardous Will occur [] Will not occur [X] **Polymerization:**

Conditions To Avoid - Hazardous Reactions

Will not undergo hazardous polymerization in normal storage conditions.

SECTION 11: TOXICOLOGY INFORMATION**Toxicological Information**

May cause sensitization by skin contact.

Chronic Toxicological Effects

Skin sensitization.

Irritation or Corrosion

Corrosive! Damages skin and eyes.

Symptoms related to Toxicological Characteristics

Skin: Contact with substance may cause severe burns to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Permanent eye damage including blindness could result.

Inhalation: Inhalation of vapors/fumes causes respiratory irritation with throat discomfort, coughing or difficulty breathing.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Phenol, 4-nonyl-, branched	84852-15-3	n.a.	n.a.	n.a.	n.a.
2. *Poly(oxy(methyl-1,2-ethanediyl)	9046-10-0	n.a.	n.a.	n.a.	n.a.
3. 1,5-Pentanediamine, 2-methyl-	15520-10-2	n.a.	n.a.	n.a.	n.a.
4. 4-tert-Butylphenol	98-54-4	n.a.	n.a.	n.a.	n.a.
5. 1,3-Benzenedimethanamine	1477-55-0	n.a.	n.a.	n.a.	n.a.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

SECTION 12: ECOLOGICAL INFORMATION

General Ecological Information

Avoid release to the environment. Do not empty into drains. May be hazardous to the environment if released in large quantities.

Results of PBT and vPvB

assessment No data available.

Persistence and

Degradability Not readily biodegradable.

Bioaccumulative

Potential No data available.

Mobility in Soil

not reported, unknown.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

SECTION 14: TRANSPORT INFORMATION
--

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name	Caustic Alkali Liquid, NOS (Polyoxypropylenediamine)(Nonyl phenol), 8, Packing group III.
DOT Hazard Class:	8
DOT Hazard Label:	CORROSIVE
UN/NA Number:	UN1719
Packing Group:	III
Precautionary Label	Corrosive! Damages skin and eyes. Avoid skin and eye contact. May cause eye and skin irritation. May cause skin sensitization. Wear protective equipment and clothing. Always read MSDS/SDS before use.

AIR TRANSPORT (ICAO/IATA)

ICAO/IATA Shipping Name	Caustic Alkali Liquid, NOS (Polyoxypropylenediamine)(Nonyl phenol), 8, Packing group III.
UN Number:	1719
Hazard Class:	8 - CORROSIVE
Packing Group:	III

MARINE TRANSPORT (IMDG/IMO)

IMDG/IMO Shipping Name	Caustic Alkali Liquid, NOS (Polyoxypropylenediamine)(Nonyl phenol), 8, Packing group III. Caustic Alkali Liquid, NOS (Modified Amido Amine)(Nonyl phenol), 8, Packing group III.
UN Number:	1719
Hazard Class:	8 - CORROSIVE
Packing Group:	III
IMDG EMS Number:	FA,SB
Marine Pollutant:	Yes

SECTION 15:REGULATORY INFORMATION
--

Regulatory Information

SARA 302 Extremely Hazardous Substances: None.

SARA 313 Toxic Chemicals: None.

CERCLA Reportable Quantity: None.

SECTION 16: OTHER INFORMATION

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

This Safety Data Sheet (SDS) is prepared by Epoxy Systems, Inc. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

PREPERATION 02/17/2015